

Duck Blind Installation Instructions

1. **Parts List**

- 1 – Bow Section (Tapered end)
- 1 – Stern Section (Squared end)
- 1 – Port Side Section

- 1 – Starboard Side Section
- 2 – Deck Rings

2. **Tools Required**

- 5/32" Hex Head Screwdriver

- ### 3. **Install Deck Rings** – Install the deck rings on the stern side of each side handle. Remove the screw, insert the deck ring between the handle and the washer, and refasten the screw.



- ### 4. **Install Bow Section** – Lay the bow section over the bow of the NuCanoe. Clip the buckles on each side of the Bow Section to the deck rings in the NuCanoe. Then loop the velcro webbing on each side through the deck ring and secure it back to itself.



- ### 5. **Install Stern Section** – Insert the webbing strap from the stern section through the stern hole, around the stern handle, and velcro onto itself. Then lay the stern section over the stern of the NuCanoe. Clip the buckles on each side of the Bow Section to the deck rings in the NuCanoe. Then loop the velcro webbing on each side through the deck ring and secure it back to itself.



- ### 6. **Connect Gunwale Straps** – Take the long strap from the stern sections of the blind, loop it through the ring on the bow section, pull tight, and velcro securely back to itself.



- ### 7. **Install Side Sections!** – Attached the side sections via the Velcro strips. The tapered section goes on the stern end.



- ### 8. **Questions or Comments?** – Please contact us at info@nucanoe.com.